

IRSA Varnishes: characteristics in short

Products	Demands 1	Glow of wood 2	Way of laying 3	Recommended primer	Wood species suitability 4	Consumption Total	Gloss effect 5	
Platinum Rollgrund Plus+ PRP		m	M, ST, I		BA,E,B,A,E,Exo	min. 100g/m ²		
Renogrund R		h	M, ST, D, I		BA,E,B,A,E,R,O,Exo	min. 100g/m ²		
Platinum Exotic Primer PEP		h	M, ST, I		BA,E,B,A,E,R,O,Exo	min 100g/m ²		
Uni Primer AL UPAL		h	M, ST, I		BA,E,B,A,E,R,Exo	min. 100g/m ²		
Platinum Spatula Gel PS		l	M, ST, I		BA,E,B,A,E	min. 60g/m ²		
Platinum 3001 1C	n	l	M, ST, F	PRP, PEP, PS, UPAL	Oak, Beech, Maple, Ash, fruit wood,Exotics	approx. 360g/m ² (6)	sm	
Platinum 3000 1C	n-h	l	M, ST, F	PRP, PEP, PS, UPAL		approx. 360g/m ² (6)	sm/g	
Platinum 2C 3055	n-vh	l/l	M, ST, F	PRP, PEP, PS, UPAL			hg	
Platinum 2C 2010/3010	n-vh	m/l	M, ST, F	PRP, R, PEP, PS, UPAL			sm	
Platinum 2C 2030/3030	n-vh	h/l	M, ST, F	PRP, R, PEP, PS, UPAL			approx. 360g/m ² (6)	um
HolzSiegel 2000/2010	n-h	h	M, ST, F, D, I, H	R			min. 300g/m ² (6)	sm/g

- 1) n = for normal wear and tear; n-h = normal to heavy wear and tear; n-vh normal to very heavy wear and tear
- 2) l = little; m = medium; s = strong;
- 3) M=mosaic parquet flooring; ST= wood strip flooring; D= floorboards; I=upright-segment parquet (less swelling and shrinking wood like oak); H= wooden pavement; F= industrial wood flooring unsealed;
- 4) BA=Bamboo, E=Oak, B=Beech, A=Maple, E=Ash, *R=Smoked oak, *O=timber wood, *Exo=Exotics, * Please consider the Technical data sheets; Apply a sample patch!.
- 5) hg = high gloss, g = glossy, sm = silky matt, um= ultra matt